

Thermoflo

PMP 098/112

**Multi-Speed Direct Drive
or
Variable Speed ECM Motor**

**Low Profile
Packaged Multi-Position
Oil Furnace**

Ratings - 2 Sizes

70,000 to 112,000 Btuh Input
0.50 to 0.80 GPH #2 Fuel Oil




Up flow or Counter flow




Horizontal - Left or Right

- ❑ AFUE's up to 86.4%
- ❑ Venting options:
 - Chimney/atmospheric
 - Direct vent (with optional kit)
- ❑ Multi-Position installation
 - High Boy (up flow)
 - Horizontal – Left or Right
 - Counter Flow (down flow)
- ❑ Stainless steel heat exchanger
- ❑ Tube style aluminized steel secondary heat exchanger
- ❑ Large front access clean-out secured with studs and nuts
- ❑ Slide-out blower/motor - easily removed for service
- ❑ Continuous fan on switch
- ❑ Burner and controls
 - Factory-wired with simple plug-in connections
 - PSC motor
 - Solid state ignitor and solenoid valve



Thermoflo


RATINGS

Model	Firing Rate	Input	Output	Direct Drive Blower (PCS)				*Energy Star Certified Variable Speed Blower (ECM) 				Maximum cooling capacity (tons)
				Blower size	Blower motor hp	Blower CFM		Blower Size	Blower Motor hp	Blower CFM Range		
						@ 0.25 WC	@ 0.50 WC			min	max	
PMP-098	0.50	70,000	58,000	10-8	1/3	860	795	10-8	1/2	750	1350	3.0
	0.60	84,000	69,000	10-8	1/3	1030	925	10-8	1/2	750	1350	3.0
	0.70	98,000	81,000	10-8	1/3	1170	1050	N/A				
PMP-112	0.68	95,200	81,000	10-10	1/2	1165	1080	10-10	1/2	900	1450	3.5
	0.80	112,000	94,000	10-10	1/2	1300	1200	10-10	1/2	900	1450	3.5

* As an Energy Star partner Thermoflo has determined that this product with Variable Speed Motor meets Energy Star guidelines for energy efficiency, Note: Filter sizes required: PMP-098 (1) 20"X20" - PMP-112 (1) 24"X24" Refer to installation manual for detailed air flow information.

PMP-098 Chimney Venting			PMP-098 Direct Vent			PMP-112 Chimney Venting			PMP-112 Direct Vent		
Burner	Input (GPH)	AFUE %	Burner	Input (GPH)	AFUE %	Burner	Input (GPH)	AFUE %	Burner	Input (GPH)	AFUE %
Beckett AFG	0.50	85.2%	Beckett NX	0.50	86.1%	Beckett AFG	0.68	85.3%	Beckett NX	0.68	85.8%
	0.60	85.1%		0.60	85.4%		0.80	85.4%		0.80	85.3%
	0.70	83.9%		0.70	84.5%	Beckett NX	0.68	85.8%	Carlin EZ-LF	0.68	85.2%
Beckett NX	0.50	86.1%				Carlin EZ-LF	0.80	85.3%	Riello 40-F3	0.68	85.8%
	0.60	85.4%				Riello 40-F3	0.80	85.4%			
	0.70	84.5%									
Carlin EZ-LF	0.50	86.2%									
	0.60	85.4%									
	0.70	83.8%									
Riello 40-F3	0.50	86.4%									
	0.60	85.9%									
	0.70	84.5%									

DIMENSIONS



Model	Furnace Casing			Warm air supply (top)		Return air (side)		Flue Pipe diam.	Shipping Weight (pounds)
	Width A	Depth B	Height C	Width D	Depth E	Width F	Depth G		
PMP-098	16-7/8	20-1/8	40-3/4	16	19	19	19	5	125
PMP-112	21-3/4	25-3/4	41-1/2	17-3/4	18-3/4	23	19	5	153

Note: Refer to installation instructions for details and proper installation.

EQUIPMENT

- Factory-assembled
- Rugged 22-gauge cabinet with powder coat finish
- Stainless steel heat exchanger
- Variable Speed ECM fan center compatible with 2-stage A/C compressors
- Continuous fan on selector switch
- High-efficiency flame retention burner (Beckett AFG or NX, Carlin or Riello)
- Easy access panel for wiring and control board access



In the interest of continual improvement in product and performance, Thermoflo reserves the right to change specifications without notice.

WARRANTY

- 20 year limited warranty on heat exchanger
- 5-year limited warranty on parts
- Optional 5 - or 10-year parts and labor warranty



Thermoflo

8201 West Calumet Road • Milwaukee, WI 53223

www.williamson-thermoflo.com

Form No. T-113 (0813)